

T-4909-AE

40
YEARS
ANNIVERSARY
EDITION

For the past 40 years, Dr. Tresky AG has been perfecting the art of creating die bonding / pick & place systems.

The **T-4909-AE anniversary edition** is a manual, budget sensitive die bonder with superior ergonomic design. As with all of Tresky's products, the **T-4909-AE** incorporates True Vertical Technology™ which guarantees parallelism between chip and substrate at any bond height. Bonding parameters and sequences, intuitively programmable by an integrated Raspberry PC with touchscreen.

T-4909-AE Application Packages:

- Epoxy
- Eutectic
- Flip-Chip

Force controlled

True Vertical Technology™

Easy to use

MICRO ASSEMBLY

T-4909-AE



TRESKY

Dr. TRESKY AG
Switzerland
tresky@tresky.com
www.tresky.com

Excellent performance, ergonomically designed and high reliability makes the **T-4909-AE** ideal for small and medium volume production.

APPLICATIONS

Die Attach, Flip-Chip, MEMS, MOEMS, VCSEL, RFID, Adhesive Bonding, Eutectic Bonding,

FEATURES AND OPTIONS

TRUE VERTICAL TECHNOLOGY™
with 95mm Z-movement

FLIP-CHIP ULTRA module
is a beam splitter optics, which
allows the simultaneous viewing
of two objects by an optical overlay
(superposition) on the monitor.
(Option)

Touchscreen for selection
of pick & place, dispensing,
stamping, mode.
Create and store custom
sequence.
E.g.: Pick, dispense and
place with automatic start of heating.

Pick & place spindle with force sensor
and 360° tool rotation. Optional: with tool heating and Scrub

Time/Pressure dispenser, stamping or preform spindle

The software displays the overlaid
beam splitter image and
is very easy to use.

XY air-cushioned placement
stage with fine adjustment
control, supporting: Waffle- / Gel-Pak -,
Substrate - Holder, various
Heating Plates.

XY-fine adjustment

TECHNICAL DATA

XY- Movement (placement stage):	180mm x 180mm (manual)
Z- Movement:	95mm (manual)
Spindle Rotation:	360° (unlimited)
Bond Force:	20g - 1000g
Placement accuracy:	±10µm (operator/process depending)
Flip-Chip Placement accuracy:	±5µm Option (operator/process depending)
Connections:	Compressed air 5 - 6 bar / Vacuum 0.6 bar (abs)
Dimensions:	755mm x 730mm x 500mm
Weight:	33kg
Voltage:	110V / 220V

Note: All specifications are subject to change without notice

Represented by



Accelonix BV
Luchthavenweg 18b • NL-5657 EB •
Eindhoven • The Netherlands •
T: +31 40 750 1650 • E: info@accelonix.nl

Headquarters

www.tresky.com

Dr. TRESKY AG
Boenirainstr. 13
CH-8800 Thalwil
Switzerland
Tel.: +41 44 772 1941
tresky@tresky.com

TRESKY Corporation
704 Ginesi Drive, Suite 11A
Morganville, NJ 07751
USA
Tel.: +1 732 536 8600
sales@tresky.com

