

	ta Report Power View 🛛									O He di linne	Power Source	i fattina I	÷.		
Seen Adud Humanel Inta 🔋 🧮 Uphat Land Humane 🔋 🔛 Oper-Drivered Analysis									Place :	100000					
4100	-31 (Killion 3.2)	2.1 (Lidlen 3.2) Voltage (M) : 206.8 V / Prequency (M) : 56.06 Ve / Observation Partial Tp : 1.5 Limin / Pickar Inguilance : 204 / Pickarmater : 2007 / Silve 🔞													
	Straph III1	Required Point	- () AC Paver 5 in	TESTON											
		Ovela			236.04.7										
	Actual Hes	nare			aneous Shot term Ficker Severty (Pd. ()) per measured data (201.01 + 1 et lib : (monovel data 33) Madamen Values					Pit.	Line 1 all of		67.5.8		
	Respond	13	14								0100400	1 10 10			
	Time (4	- 48	1.0						Level (PR) 1 8.4	Int	Phase Shifts	1.00			
5	Volume BHS 7/2	224.49						n			During Detection	: Series I Continues I RMS I Neckral			
	Pd.()		13						Limit (Psil) :						
	6.01%	- 1						14							
	draw (17%)	- 1	2.4						timit (dc): 3.	3					
	Transition	- 1	5.41					0(19)							
	Madmum per		6.10						Linit (dmax) i	4	DPA SOON	1 20 10			
	(2)							dinas (%)				1 107 102 102			
	dogs [b]	-							Limit (Tmax): 6.	5					
	True (c)		1.0					Tree(b)							
	Last mea	100	1.1				+	next							
	P4														
				41 12	5 25	281 351	46 55								
	reta				Test r	uning (Simulatur)				re brend an					
-		87% rename : 00 : 00 : 127													
and 1		b. Stort Store								Safi 00:00:52					

# **MAIN FEATURES**

- Flicker Emission Measurements
- IEC 61000-3-3, IEC 61000-3-11 and many others
- Large library with pre-programmed tests
- Easy generation of comprehensive test reports
- Enhanced analysis for root cause analysis
- Pst, Plt, dc, dmax and Tmax evaluation

# **CTS 23 - Flicker Measurement** Compliance Test Studio

Compliance Test Studio 23 for Flicker is the comprehensive and easy to use software to perform flicker emission measurements with a DPA 50xN power analyzer. All relevant flicker parameters (Pst, Plt, dc, dmax, Tmax) are assessed. It supports you for basic PASS / FAIL testing, report generation and enhanced analysis of measurement data. This makes it the ideal tool for compliance testing as well as measurement during the product development process.

le	Data	Report	Power Vi	w									0	) Help 🔺 Ha	me	Power Source		ê
Generate	Report	Open Rep	ort Setup 🍫 Oj	ien Report Manaj	ger											Device : Mode :	: External source : AC	2
61000-3-	-3 (Edition :	3.2) Vol	age (Vn) : 230.0	V Prequen	cy (fn) : 50.00	D Hz   0	Observation Pe	riod Tp: 10 x 1 min	n   P	Plicker Impeda	nce : Zref	Fildvermeter :	2307/	SOHz 🕘		System :	: 1Line	
																DPA 503N Frequency	: 50 Hz	^
	🎢 Grapi	h III Table														Connected AIF	: AJF 503N32.4	
					Sh	nort-term	Flicker Severt	ty (Pst)						Pst	-1			
	1											Pst = 0.	392	Data				
														Result				
	0.8																	
	ž 0.6																	
	0.4																	
	0.2																	
	0																	
		1	2 3 4	5 6 7	8 9	10	Measurement I	ndex										
					Lo	ong-term	Flicker Severt	ty (Pit)										
	1 # 0.5											Pit = 0.	519					
		_												Pass				
sureme	nts					Те	est finished (Sim	ulation)					Time	(h:min:s)				
ain :		0					100%							sin: 00:00:				
tual :	1	10				s	tart	Stop					actus	al: 00:11:	: 07			

### Efficient testing with Standards Library

Increase your efficiency by using the extensive test library. Spend time with testing and not with programming.

andards Library Device Mode User Tests Reports	Power Source
defined Custom Recent	Device : External source Mode : : AC System : : Lline
e	Name : · DPA 503N
ndustry	
<ul> <li>International</li> </ul>	
> DIN	
> 68	Phenomenon : -
V IEC	
> 61000-3-2	Type: -
× 61000-3-3	Duration : -
<ul> <li>Edition 3.2</li> </ul>	Line: -
<ul> <li>230V / 50Hz System</li> </ul>	Cycles : -
F General Test conditions	Cyois: -
Annex A - Special Test conditions	
F Annex B - dmax voltage changes caused by manual switching	
> 120V / 50Hz System	
> 100V / 50Hz System	
> Edition 3.1	
> Edition 3	
✓ 61000-3-11	
> Edition 2	
> Edition 1	
> 61000-3-12	
> 61000-4-13	
> JIS	

Using the standards library for testing is a convenient way to get started quickly. Select one of the pre-programmed tests, adjust the basic settings and start the test. The Flicker library covers a wide range of standards, including IEC 61000-3-3 and IEC 61000-3-11. It includes not only the current but also the older editions of standards which ensures backward compatibility of products.

AMETEK CTS experts actively participate in international standardization work. This ensures that always the latest changes are implemented and newest versions of standards are available. Updates are regularly released to keep track with changes in standards, methods or test conditions.




Specifications subject to change without notice. Ametek CTS is an ISO accredited Company. Products are designed and manufactured under strict quality and environmental requirements of ISO 9001.

## **Compliance Test Studio**



### Main Features and Functions





# lahla Liconaa

The Measure&Analyze function allows fully compliant testing of IEC 610003-3, IEC 61000-3-11 and related standards. Tests according to standard test conditions and special test conditions (e.g. air conditioners, refrigerators, manual switching) are implemented. The software automatically checks all the conditions for emission limits (Pst, Plt, dc, dmax, Tmax) and delivers a PASS / FAIL decision. This allows also less experienced users to perform fully normative tests.

Emission limits and test settings can be adjusted for precompliance measurement, e.g. during product development.

Documentation of flicker measurements is an important step in testing. Compliance Test Studio supports with various functions for report generation: add customer information, test object data, test setup pictures and additional information. With the report editor the report content can be customized to create a meaningful report. Customize the test report template to include your company logo and address. Monitoring measurements and print screens of external instruments can also be added.

It is also possible to save the report within the Compliance Test Studio and reopen to modify. The report can be exported in various file formats which allows further processing and integration in overall test reports..

The CTS.EnhancedAnalysis license offers additional tools for further analysis of measurement data. Get detailed insights into Pinst values, trend analysis over time and min/max value analysis.

This license also allows to post process saved test files. Like this it is possible to re-analyze already taken measurements e.g. to change the standard or test condition without retesting. This saves valuable test time which is specifically helpful with flicker tests that last usually two hours.

Available Licenses	
License	Description
CTS.DeviceDPA	Enables the Device Mode to perform harmonics and flicker measurements with a DPA 50xN,
(inlcuded with every DPA 50xN)	one license required per device
CTS.ExtFunctions	Extended features including report, link, flowchart, measuring instruments, iteration,
(inlcuded with every DPA 50xN)	interlink, import and export of test data, requires a device license
CTS.Industry	Library with pre-programmed tests for industry standards (IEC, GB, BS, DIN, including IEC
(inlcuded with every DPA 50xN)	61000-3-2/-12 harmonics and IEC 61000-3-3/-11 flicker), valid for all licensed devices,
	requires a device license
CTS.Automotive-H&F	Library with pre-programmed tests for harmonics and flicker automotive standards (e.g. ECE
	R10, IEC 61851, Stellantis, Volkswagen, Mercedes, etc.), special licenses for Nissan and
	Renault on request, valid for all licensed devices
CTS.EnhancedAnalysis	Enhanced analysis function with detailed view on measurement data per time window,
	analysis of saved test result files, re-evaluate existing measurements
Supported Devices	
Models	DPA 500N_DPA 500N1_DPA 500N1_1_DPA 503N

#### DPA 500N, DPA 500N1, DPA 500N1.1, DPA 503N



Specifications subject to change without notice. Ametek CTS is an ISO accredited Company. Products are designed and manufactured under strict quality and environmental requirements of ISO 9001.

10 June 2024

