

CN 200N1

AUDIO TRANSFORMER ASSEMBLY FOR LF CONDUCTED IMMUNITY TESTING



FOR TESTS ACCORDING TO ...

- › AIRBUS
- › BMW GS 95023
- › Chrysler CS-11809 (2009)
- › DaimlerChrysler DC-10615
- › DO 160 Section 16
- › DO 160 Section 18
- › Ford FMC1278
- › GLloyd VI-7-2
- › ISO 11452-10
- › Jaguar EMC-CS-2010JLR V1.1 (2011-01)
- › Jaguar JLR-EMC-CS V1.0 Amd 4
- › LV 123
- › MIL STD 461 G CS 101
- › MIL STD 461 G CS 109
- › MIL-STD-704
- › Mitsubishi ES-X82115
- › SAE J1113-2
- › Tata TST/TS/WI/257
- › VW 80300
- › VW 80303

CN 200N1 - SINGLE-BOX TRANSFORMER ASSEMBLY FOR LF CONDUCTED IMMUNITY TESTING

The CN 200N1 is a standalone coupling network unifying two audio transformers being individually configurable for various test requirements (e.g. Ford FMC1278, German Lloyd GL VI-7-2 and SAE J1113-2). The CN 200N1 is used to apply the test signals to the lines under test via an audio transformer to perform ripple voltage tests and continuous or transient conducted immunity tests.

HIGHLIGHTS

- › **One-box transformer and 0.5 ohm load assembly**
- › **Frequency response 10 Hz to 250 kHz**
- › **Secondary saturation 50 A per transformer**
- › **Audio power 2 x 200 W**
- › **Freely configurable on primary/secondary; serial, parallel, single**
- › **Turns ratio 2:1 step down**
- › **Built-in non-inductive load resistor 0.5 ohm, 250 W**

APPLICATION AREAS



AUTOMOTIVE



MILITARY



AVIONICS

TECHNICAL DETAILS

TECHNICAL DETAILS

CHARACTERISTICS AUDIO ISOLATION TRANSFORMERS

Frequency response	10 Hz - 250 kHz
Audio power	200 W
Secondary saturation	Max. 50 A AC or DC
Turns ratio	2:1 step down

TRANSFORMER CONFIGURATION

Primary configuration	Single, series or parallel connection
Secondary configuration	Single or parallel (with 0.5 ohm, 250 W load)

CONNECTORS

Primary connectors	4 mm safety lab connectors
Secondary connectors	High current safety connectors

GENERAL DATA

GENERAL DATA

Dimensions	19", 3 HU (395 mm x 449 mm x 133 mm)
Weight	Approx. 24 kg
Cooling	passive cooling
Temperature	10°C - 40°C
Rel. humidity	Max. 85%, non-condensing
Atmospheric pressure	86 kPa (860 mbar) to 106 kPa (1 060 mbar)

COMPETENCE WHEREVER YOU ARE



CONTACT EM TEST DIRECTLY

Switzerland

EM TEST (Switzerland) GmbH > Sternenhofstraße 15 > 4153 Reinach > Switzerland
 Phone +41 (0)61/7179191 > Fax +41 (0)61/7179199
 Internet: www.emtest.ch > E-mail: sales.emtest@ametek.com

Germany

AMETEK CTS Germany GmbH > Lünener Straße 211 > 59174 Kamen > Deutschland
 Phone +49 (0)2307/26070-0 > Fax +49 (0)2307/17050
 Internet: www.emtest.com > E-mail: info.cts@ametek.de

France

EM TEST FRANCE > Le Trident - Parc des Collines > Immeuble B1 - Etage 3 > 36, rue Paul Cézanne > 68200 Mulhouse > France
 Phone +33 (0)389 31 23 50 > Fax +33 (0)389 31 23 55
 Internet: www.emtest.fr > E-mail: info@emtest.fr

Poland

EM TEST Polska > ul. Ogrodowa 31/35, 00-893 Warszawa > Polska
 Phone +48 (0)518 64 35 12
 Internet: www.emtest.com/pl > E-mail: infopolska.emtest@ametek.com

USA / Canada

AMETEK Compliance Test Solutions > 52 Mayfield Ave. > Edison > NJ 08837
 Phone +1 (732) 417-0501
 Internet: www.emtest.com > E-mail: sales.emtest@ametek.com

P.R. China

E & S Test Technology Limited > Rm 913, Leftbank >
 No. 68 Bei Si Huan Xi Lu > Haidian District > Beijing 100080 > P.R. China
 Phone +86 (0)10 82 67 60 27 > Fax +86 (0)10 82 67 62 38
 Internet: www.emtest.com > E-mail: info@emtest.com.cn

Republic of Korea

EM TEST Korea Limited > #405 > WooYeon Plaza > #986-8 > YoungDeok-dong > Giheung-gu > Yongin-si > Gyeonggi-do > Korea
 Phone +82 (31) 216 8616 > Fax +82 (31) 216 8616
 Internet: www.emtest.co.kr > E-mail: sales@emtest.co.kr

Information about scope of delivery, visual design and technical data correspond with the state of development at time of release. Subject to change without further notice.