

VSS 500N15.3

VOLTAGE SURGE SIMULATOR WITH 0.5J CONSTANT ENERGY



FOR TESTS ACCORDING TO ...

- › EN 60255-27
- › EN 60255-5
- › IEC 60255-27
- › IEC 60255-5
- › IEC 61180-1
- › IEC 62052-11

VOLTAGE SURGE SIMULATION

The surge simulator type VSS 500N15.3 generates high voltage transients as required by IEC 60255-27 with a source impedance of 500 ohm for transient overvoltage tests on "Protection Relays". The output voltage ranges up to 15 kV, divided into two voltage ranges (up to 6.6kV and up to 15kV).

The no-load waveshape corresponds to IEC-61180-1. For this kind of testing the IEC 60255-27 standard requires a fixed energy of 0.5 J at each test level.

HIGHLIGHTS

- › Test pulse 1.2/50 μ s up to 15 kV as per EN/IEC 60255-27
- › 7 different test levels
- › Source impedance 500 ohm
- › Constant energy of 0.5 J at each test level
- › Peak voltage measurement
- › Peak current measurement
- › Interlock

APPLICATION AREAS



COMPONENTS



INDUSTRY



RESIDENTIAL

TECHNICAL DETAILS

**VOLTAGE SURGE SIMULATOR, PULSE
1.2/50 US AS PER EN/IEC 60255-27**

TECHNICAL DATA

Voltage (o.c.)	250 V - 15,000 V $\pm$ 10 %
Front time	1.2 μ s $\pm$ 30 %
Time to half value	50 μ s $\pm$ 20 %
Source impedance	500 ohm
Energy	0.5 J $\pm$ 0.05 J at each test level
Test level	0.55, 1.0, 3.0, 5.0, 6.6, 9.3 and 14 kV
Pulse forming	As per IEC 60255-27, (replaces -5)
Polarity	Positive, negative or alternating
Event counter	1 - 30,000 or endless

TRIGGER

Trigger of events	Automatic, manual, external
CRO trigger	5V trigger signal for oscilloscope
Synchronisation	0° - 360°, resolution 1°
Repetition rate	1 s - 999 s, depending on the voltage

OUTPUT

Direct	Via HV connector; Zi = 500 ohm To connect external test boxes or devices
Output 1	500V - 6,600 V
Output 2	6,600 - 15,000 V

MEASUREMENTS

Peak voltage	15,000 V in the LCD display
Peak current	30.0 A in the LCD display

TEST ROUTINES

Quick Start	Immediate start; easy-to-use and fast
User Test routines	Change polarity after n pulses, Change voltage after n pulses, Change phase angle after n pulses
Standard Test Routines	As per IEC 60255-27
Service	Service, setup, self test

INTERFACE

Optical interface	Opto link, 3 m cable USB A connector
Parallel interface	IEEE 488, addresses 1 to 30

SAFETY

Safety circuit	Control input (24 Vdc)
Warning lamp	Floating output contact

GENERAL DATA

Dimensions, weight	19"/6 HU, 24.9 kg
Supply voltage	115/230 V $\pm$ 10/-15 %
Fuses	2xT2 AT (230 V) or 2xT4 AT (115 V)

OPTIONS

HV Contacts	Pair of gun-type HV contacts for safe application of the HV pulses to the DUT
iec.control	Remote control and documentation software, including standard test routines and reporting capabilities.

COMPETENCE WHEREVER YOU ARE



CONTACT EM TEST DIRECTLY

Switzerland

EM TEST (Switzerland) GmbH › Sternenhofstraße 15 › 4153 Reinach › Switzerland
Phone +41 (0)61/7179191 › Fax +41 (0)61/7179199
Internet: www.emtest.ch › E-mail: sales.emtest@ametek.com

Germany

AMETEK CTS Germany GmbH › Lünener Straße 211 › 59174 Kamen › Deutschland
Phone +49 (0)2307/26070-0 › Fax +49 (0)2307/17050
Internet: www.emtest.com › E-mail: info.cts@ametek.de

France

EM TEST FRANCE › Le Trident - Parc des Collines › Immeuble B1 - Etage 3 › 36, rue Paul Cézanne › 68200 Mulhouse › France
Phone +33 (0)389 31 23 50 › Fax +33 (0)389 31 23 55
Internet: www.emtest.fr › E-mail: info@emtest.fr

Poland

EM TEST Polska › ul. Ogrodowa 31/35, 00-893 Warszawa › Polska
Phone +48 (0)518 64 35 12
Internet: www.emtest.com/pl › E-mail: infopolska.emtest@ametek.com

USA / Canada

AMETEK Compliance Test Solutions › 52 Mayfield Ave. › Edison › NJ 08837
Phone +1 (732) 417-0501
Internet: www.emtest.com › E-mail: sales.emtest@ametek.com

P.R. China

E & S Test Technology Limited › Rm 913, Leftbank ›
No. 68 Bei Si Huan Xi Lu › Haidian District › Beijing 100080 › P.R. China
Phone +86 (0)10 82 67 60 27 › Fax +86 (0)10 82 67 62 38
Internet: www.emtest.com › E-mail: info@emtest.com.cn

Republic of Korea

EM TEST Korea Limited › #405 › WooYeon Plaza › #986-8 › YoungDeok-dong › Giheung-gu › Yongin-si › Gyeonggi-do › Korea
Phone +82 (31) 216 8616 › Fax +82 (31) 216 8616
Internet: www.emtest.co.kr › E-mail: sales@emtest.co.kr

Information about scope of delivery, visual design and technical data correspond with the state of development at time of release. Subject to change without further notice.