

HI-6023 Electric Field Probe with Field-Replaceable Battery

ETS-Lindgren model HI-6023 is a battery-operated electric field probe with a frequency response of 10 kHz to 1 GHz.



Key Features

Frequency Response: 10 kHz to 1 GHz

Dynamic Range: 2.0 to 800 V/m

Provides Individual and Summed Axis Values

A2LA Accredited Calibration Report

Suitable for MIL Standard Specs:

MIL-STD 461F Radiated Susceptibility (RS)

Suitable for Automotive Specs¹:

SAE J1113/27

GMW 3091/3097/3103

Suitable for Commercial Specs:

EN/IEC61000-4-3 Radiated Immunity

Operates with Most 3rd Party Immunity Software

[Watch Product Video](#)

¹ For High Field and High Frequency Requirements, the HI-6053 is Recommended

ETS-Lindgren's Model HI-6023 RF Field Probe is a fully intelligent sensor enabling fast and accurate EMF measurements with industry-leading performance specifications. Optical coupling to a variety of readout options makes this probe ideally suited for a wide range of field monitoring applications.

Designed to be single range reading, the HI-6023 can read data continuously over the entire dynamic range. Data values for each axis (X, Y, and Z) can be read individually or summed.

A unique feature of the HI-6023 is the field-replaceable battery. This battery allows the user to replace the battery when necessary, without requiring additional calibration. Simple in-field synchronization of the HI-6023 is all that is required for proper battery level monitoring.

The EMCenter Modular RF Platform along with the EMSense interface card can be used with the HI-6000 series field probes as a field monitor in addition to its capability as a system level platform.

For direct connection to a PC, either the HI-4413P Serial or the HI-4413USB interfaces are available.

Specifications

View the HI-6023 Electric Field Probe with Field-Replaceable Battery technical specifications below

Physical Specifications

Physical Interface: Duplex Optical Fiber (200 Micron Multimode); FSMA Connectors. Integral 1m Optical Cable

Battery: 4.8 V NiMH, up to 8 Hours of operation

Battery Charger: 100-240 VAC Universal Input; 3-Hour Charge from Full Depletion

Cubical Housing Height: 32 mm (1.26 in)

Sensor Protection Caps Height: 32 mm (1.25 in)

Weight: 80 g (2.82 oz)

Mounting: 1/4" 20 - UNC Internal Thread

Electrical Specifications

Detection: Isotropic (X, Y and Z Axis Readings)

Frequency Range: 10 kHz to 1 GHz

Frequency Response:

- 10 kHz to 30 kHz +0.5, -2.5 dB
- 30 kHz to 1 GHz 1.0 dB

Frequency Response with Correction: 10 kHz to 1.0 GHz 0.9 dB

Dynamic Range: 2 to 800 V/m (Single Range)

Resolution: 0.01 V/m

Isotropic Deviation: 0.5 dB @ 400 MHz

Linearity: 0.5 dB (2-800 V/m)

Sample Rate (Typical): 70 Samples/Second Maximum

Overload Withstand: >1500 V/m CW

Product Options

- Optical Modem for Connection to PC Serial Port (HI-4413P)
- Optical Modem for Connection to PC USB Port (HI-4413USB)
- EMCenter Interface Card (125446)
- Optical Cable Extensions to 50 m (H-491106-xx)
- Probe Stand Assembly (H-491269)
- Extra Probe Carriers for Above Probe Stand (H-491276)

Product Configuration

- HI-6023 Probe
- A2LA Traceable Calibration Report
- Carrying Case
- Bulkhead Connector (2)
- Fast Battery Charger/Battery Synchronizer
- 10 m Optical Cable
- Spare Screws for Battery Hatch
- Manual

Charts

View the [HI-6023 Electric Field Probe with Field-Replaceable Battery](#) charts below