




CBA 6G-120D 1.8 GHZ TO 6 GHZ 120 WATT SINGLE BAND POWER AMPLIFIER



- Compact Design
- Touch Screen Color Display
- Input Overdrive Protection
- USB, Ethernet, GPIB and RS232 Interface
- Built in Calibrated Directional Coupler

New, high power density, design has allowed us to produce a 120 watt, 1.8GHz to 6GHz amplifier in a compact 7U package. With a minimum of 100 watts of linear power this amplifier is ideal for RF immunity testing in a GTEM Cell or with a wide range of available horn antenna such as the Teseq BHA range. Readily integrated with the Teseq ITS6006 80MHz to 6GHz test system these amplifiers can form part of a broadband test system. The new touch screen colour display gives an immediate visual indication of forward and reverse power along with the current operating status of the amplifier and access to diagnostic information such as gate current and heatsink temperature.

Fan speed adjusts depending on heatsink temperature thus ensuring the minimum audio noise level possible in the operating environment. The inbuilt calibrated forward power coupler provides a quick and easy way to monitor forward power with any power meter. Multiple remote interfaces are available as standard including USB, GPIB, RS232, Ethernet.







CBA 6G-120D 1.8 GHZ TO 6 GHZ 120 WATT SINGLE BAND POWER AMPLIFIER



Key Parameters	
Frequency	1.8 GHz to 6.0 GHz
Saturated Power	120 Watts (minimum)
Power at P1 dB	100 Watts (minimum)
Gain	50 dB
Gain Flatness	+/-3 dB (maximum)

Additional RF Data		
Harmonics at 100 W	-20 dBc	
Maximum Input without Damage	+15 dBm	
Spurious	-70 dBc	
Stability	Unconditionally stable	
Load VSWR without damage (All Phase Angles)	Infinite	
Load VSWR without fold back (All Phase Angles)	Infinite	
RF Input	Type N (socket)	
RF Output	Type N (socket)	

Impedance/VSWR	
Output Impedance	50 Ω
Input VSWR	2:1
Output VSWR	2.3:1

Interfaces and Electrical	
Interface	Touch screen, GPIB, RS232, Ethernet & USB
Safety Interlock	Rear Panel Mounted BNC-female
Supply Voltage	90-264 Vac
Supply Frequency	47–60 Hz
Supply Power Requirement	<1.4 kVA

Physical and Environmental	
Dimensions	7U, 19 Inch Rack width, 615 mm deep
Weight	50 kg
Temperature Operational	0°C-40°C
Temperature Non Operating	-40°C-70°C
Humidity (Non Condensing)	95%

Options: To be specified at time of ordering		
Rear Panel RF Connectors	CBA 6G-120D-10	
Front Panel RF Connectors	CBA 6G-120D	

CONTACT US!

We're there where you need us. See details on the last page.





OUR SALES & SERVICE CENTERS

China

AMETEK Commercial Enterprise (Shanghai) Co. Ltd.

Beijing Branch
Western Section, 2nd Floor
Jing Dong Fang Building (B10)
Chaoyang District
Beijing, China, 100015
T +86 10 8526 2111
chinasales@ametek.com

Shanghai Office:

Part A1, A4, 2nd floor, Building No. 1 No. 526 Fute 3rd Road East Pilot Free Trade Zone, Shanghai 200131, China T +86 21 5868 5111

Guangzhou Office:

Room 1410-12, Yian Plaza 33 Jian She Liu Ma Road Guangzhou, China T +86 20 8363 4768

Germany

AMETEK CTS Europe GmbH

Lünener Straße 211 59174 Kamen, Deutschland T +49 2307 26070-0 sales.cts.de@ametek.com

Great Britain

AMETEK (GB) Ltd. t/a Teseq

5 Ashville Way, Molly Millars Lane Wokingham Berkshire RG41 2PL Great Britain T +44 845 074 0660 ametekgb.service@ametek.com

The contacts of our global distribution partners could be found at www.teseg.com

Japan

AMETEK Co. Ltd. Tokyo office

3rd floor, Shiba NBF Tower, 1-1-30 Shiba-Daimon, Minato-ku Tokyo, 105-0012, Japan T +81 3 6809 2401 cts-japan.sales@ametek.com

Nagoya Office

1-329 Kifune Meito-ku Nagoya-shi Aichi-ken, 465-0058, Japan T +81 52 709 5501

Poland

AMETEK CTS Europe GmbH

Biuro w Polsce ul. Ogrodowa 31/35 00-893 Warszawa, Polen T +48 518 643 512 infopolska.cts@ametek.com

Singapore

AMETEK Singapore Pte. Ltd.

No. 43 Changi South Avenue 2 #04-01 Singapore 486164 T +65 6484 2388 singaporesales.cts@ametek.com

Taiwan

AMETEK Taiwan Corp. Ltd.

10F-5, No. 120, Sec 2, GongDaoWu Rd., Hsinchu City 30072, Taiwan T +886 3 57 5099 taiwan.sales.cts@ametek.com

USA

AMETEK CTS US

52 Mayfield Avenue Edison, New Jersey 08837, USA T +1 732 417 0501 Toll free: +1 888 417 0501 usasales.cts@ametek.com

CARE TO LEARN MORE ABOUT AMETEK CTS.

With service and sales centers in Germany, Switzerland, China, Japan, Singapore, the USA and Great Britain, and accredited labs across the globe, we're where you need us.



GET MORE INFO ABOUT US AT: www.ametek-cts.com

