



Essential Apparatus for Performing Tests in accordance with MIL-STD-461D/E/F/G

Type No.	Description / page links	CE 101	CE 102	CS 101	CS 106	CS 109	CS 114	CS 115	CS 116	RE 101	RE 102	RE 103	RS 101	RS 103	RS 105
2125-1	'Wye' Capacitor Assembly, 500 VAC			X	X										
2810-106R	10 µF Bypass Capacitor			X	X										
2854-2	Transient Pulse Generator				X										
2925-1	Calibration Fixture								X						
6220-1B	Audio Isolation Transformer, 50 A			X		X									
6220-2A	Audio Isolation Transformer, 100 A			X		X									
7032-1	Isolation Transformer, 115 V, 800 W			X	X	X									
7032-2	Isolation Transformer, 230 V, 800 W			X	X	X									
7032-3	Isolation Transformer, 115 V/230 V 800 W			X	X	X									
7334-1	Loop Sensor									X					
8525-1	5 Ω Resistive Load				X										
9117-5-TS-50-N	LISN, 5 µH, 50 A		X ¹	X ¹											
9123-1N	Current Probe, 10 kHz-500 MHz							X	X						
9215-1N	Current Probe, 20 Hz-500 MHz						X								
9125-1	Calibration Fixture						X	X	X						
9133-1	'Delta' Capacitor Assembly, 270 VAC			X	X										
9142-1N	Current Injection Probe, 2 MHz - 500 MHz						X	X	X						
9144-1N	Current Injection Probe, 4 kHz - 100 MHz						X								
9146-1	'Wye' Capacitor Assembly, 270 VAC			X	X										
9207-1	Current Probe, 20 Hz - 200 MHz	X				X								X	
9224-1.0	Precision Resistor, 1.0 Ω	X													
9225-0.5	Precision Resistor, 0.5 Ω			X											
9226-0.5	Precision Resistor, 0.5 Ω					X									
9229-1	Loop Sensor													X	
9230-1	Radiating Loop													X	
9233-50-TS-50-N	LISN, 50 µH, 50 A	X	X	X	X		X	X	X	X	X		X	X	X
9335-2	Multiple Impedance Coupling Clamp								X						
9354-2	Transient Pulse Generator								X						
9355-1	Pulse Generator							X							
9401-1	10 pF Series Capacitor										X				
9410-1	High Voltage Attenuator, 50/50 Ω							X	X						
9454-1	High Voltage Attenuator, 50/600 Ω								X						
9533-1	Voltage Probe		X												
9554-10K/100K	Variable Frequency Module								X ³						
9554-100K/1M	Variable Frequency Module								X ³						
9554-1M/6M	Variable Frequency Module								X ³						
9554-6M/50M	Variable Frequency Module								X ³						
9554-50M/100M	Variable Frequency Module								X ³						
9841-1	50 Ω High Voltage Load	X	X						X ³		X				
9863-1	'Delta' Capacitor Assembly, 500 VAC			X	X										
9917-0.1	Precision Resistor, 0.1 Ω													X	
21210-1.5	1.5 Ω Series Resistor													X ⁴	

X¹ Used for measurements starting at 150 kHz when specified

X² High pass filters can be supplied up to 50 MHz, 50 Ω. Band reject filters can be supplied up to 50 MHz, 50 Ω.

X³ Required to for critical frequencies beyond minimum requirements

X⁴ Required when using **Type 8850-2** or **Type 2352-2**

